

12.8V200Ah

LFP LI-ION BATTERY (LONG LIFE)





Dimension:





SAFETY

- Prismatic LFePO4 cells, Longer cycle life and much more safety.
- + UN38.3, CE certification for system.
- + The cycle life over 3000 times @80%DOD

DESIGN

- + ABS container, replace VRLA battery perfectly. .
- + Fast charge performance,
- + -20~+55°C widely temperature range.
- + Maintenance free.

BATTERY MANAGEMENT SYSTEM (BMS)

- + Integrated BMS inside.
- + Independent protection for charge and discharge.
- + OVP, LVP, OTP, LTP, OCP, Short circuit protection.

Unit: mm

Ritar International Group Ltd. Shenzhen Ritar Power Co., Ltd. 10th Floor, Tower C, 1st Building, Software Industry Base, No.81, Xuefu Road, Nanshan District, Shenzhen City, Guangdong Province, PRC

For more information, contact with: sales@ritarpower.com



12.8V200Ah

Specification

Part Number	8010128020001
Model	R-LFP12.8V200AH
Nominal Voltage [V]	12.8
Nominal Capacity [Ah]	200
Total Energy [Wh]	2560
Max. Charging Current [A]	100
Recommended Charging Current [A]	100
Charging Voltage [V]	14.6
Max. Discharging Current [A]	100
End of Dicharge Voltage [V]	11.2
Pulse Discharge Current	400A@ 10S
Dimension (W*D*H, mm)	522*240*219
Weight [Kg]	25.2
Operation Humidity	0~95% RH (No condensing)
Operating Temperature Range	Charge: 0~+45℃; Discharge: -20~+55℃
Protection	Over charge, Over discharge, Over current, Over temperature, Low temperature, Short circuit
Parallel Support	Yes, Max. 2 Pcs
Series Support	Yes, Max. 4 Pcs.
Cycle Life ¹	>3000 cycles
Designed Calendar Life	>10 Years

Note: 1. 80% DOD and to 80% of initial capacity.

The datasheet is subject to change without prior notification

For more information, contact with: sales@ritarpower.com

10th Floor, Tower C, 1st Building, Software Industry Base, No.81, Xuefu Road, Nanshan District, Shenzhen City, Guangdong Province, PRC