



STRP250



Cell Number: 60

Solar Cell Type: Polycristal Energy Class: 250 Wp

Efficiency Warranty On A Yearly Basis

- First 10 years 90% efficiency warranty
- 25 years 80% efficiency warranty

Highly Efficient Modules

- Maximum power match with positive tolerance till 5 watt.
- Simple compability with our solution partner inverter producer products to reach maximum system output power

Quality Test - Product Warranty

- Certificates given by national and International Standard associations.
- 10 years of product warranty
- Product structure is created to withstand the toughest environmental conditions.

Flexible Design

- Its ideal for applications that are available for all roof and flor
- System is suitable to connect grid or power supply.
- Suitable for using on ungrounded photovoltaic arrays.



WATT POZITIVE TOLERANCE



YEAR PRODUCT WARRANTY


























STR P250

MODELS		
		STR P 250
ELECTRICAL FEATURES		
Nominal Power	Pmax (Wp)	250
Nominal Power Tolerance	Pmax (Wp)	-0/+5
Nominal Power Voltage	Umpp (V)	31.28
Nominal Power Current	Impp (A)	8.01
Short Circuit Current	Isc (A)	8.66
Open Circuit Voltage	Voc (V)	37.66
Max. System Voltage	(V)	1000
Diode Current	(A)	15
Standard Test Conditions	(STC) Radiation 1000W/m2	, AM: 1,5 Temp. 25 C

TECHNIC INFORMATIONS		
Cell Number (Matrix)	60 (6 x 10)	
Cell Type	Polycrystalline	
Cell Size (mm)	156 x 156	
Panel Size LxWxH (mm)	1665 x 1001 x 42	
Weight (kg)	19	
Connection Type	Tyco / MC	
TEMPERATURE PARAMETER		
NOCT	C°	+46 +2
Temperature Parameter	Isc (%/K)	+0.05
Temperature Parameter	Uoc (%/K)	-0.32
Temperature Parameter	Pmax (%/K)	-0.43





25 Year Efficiency Warranty



Increase of Efficiency and Decrease of Current Loss



Norm Energy Systems Ltd.

PERPA Trade Center, Block-B 11th Floor, No: 1845-1847 Okmeydani Sisli-ISTANBUL, TURKEY Zip Code: 34384 Phone: +90 (212) 444 0 941 / Fax: +90 (212) 320 29 33

Gsm & Mobile: +90 (532) 563 14 50

www.normenerji.com.tr