

## LED LUMINARY EARTH SERIES/ 64 LED PROJECTORS



64 LED SERIES



IP66



PFC

PFC FONKSİYONLU  
LED DRIVER

COMM® life is over 60,000 hours of LED lighting fixtures. These fixtures are about 20 times more life compared to conventional lighting fixtures, energy consumption and maintenance costs are minimized.

### Advanced Applications:

Building Facade Lighting  
Factory Lighting  
Billboards Lighting  
Large Common Area Lighting  
Scaffolding Lighting  
Tower Lights

### Quality Documents:

- EN 60598 2-5
- ISO 9001
- ISO 14001
- OHSAS 18001
- CE

### General Protection

Features: Led Open Circuit Protection  
Led Short Circuit Protection  
Over and Under Voltage Protection  
Soft Start Function  
Thermal Protection Feature





**EARTH SERIES/ COMM-64-P150  
TECHNICAL INFORMATION**

Model	COMM-64-P150
Power	150W
Input Voltage	100-240V AC 50/60 Hz
Power Factor	>0,97
Number of LEDs	64 Pcs
Lumen	>14600 Lumen
Color Temperature	4000-5000-6500 Kelvin
Led Life (LM80)	>60.000 Hours
Operating Temperature	-40 / +75 C°
Color rendering (CRI)	>70
Lighting Angle	125°
IP Protection Class	IP66
Body Material	Aluminum Injection
Front Section	4mm Tempered Glass
Foot Mounting Screw Diameter	10mm
Bracket Screw Between Diameter	150mm
Weight	8,7 kg
Dimensions (AxBxC)	35 x 50 x 9 cm
Color Options	Desired Color Options Workable

Renk Seçenekleri

RAL Kod:



- ✓ 3-5 Year Product Warranty (Standard 3Year + 2yl Optional)
- ✓ Economic Initial Investment Cost
- ✓ IP 66 Protection
- ✓ Special Absorbing Box
- ✓ Limiting Glare Special to Reflector
- ✓ Stability in Light Source Color
- ✓ Different Light Source Different Color Options
- ✓ 3000K-4000K-5000K-6500K
- ✓ LM80 and TM21 60.000Saat by Standard Life
- ✓ Measurements by Standard EN60598
- ✓ Different optical Options
- ✓ IESNA-79-08 Photometric Measurements by standard
- ✓ High Quality PCB Connectors
- ✓ Powder Coating
- ✓ High Quality Fittings